

Now With
 **ONYX**
(optional)

GZC 3202SG (25PL / 10PL)



Introducing
SPECTRA
Starfire Print Head
(25PL / 10PL)

Main Features

Two Starfire heads with speed up to 129m²/hr.

Smaller but stronger and more precise body.

Revolutionary print head with Redijet tech.

Easy-maintenance positive pressure system.

More humanized media feeding system.


Accurate pneumatic shaft taking up system.





GZM+ 3202

Gongzheng High Speed Printer
SPECTRA STARFIRE



AD 1802S

Gongzheng ECO SOLVENT PRINTER
Real Variable Dot Technology



A wide range of applications solution!

With continuous ink recirculation and robust repairable construction, **Dimatix Starfire 1024** print head delivers unparalleled saturation and smooth gradient.



Positive pressure system with ink basket!

Positive pressure system with ink basket is easy maintaining and assures stable and fluent ink delivery.



Self-developed drying system!

Ceramic-core thermal drying system controlled by industrial power switches, treats the printing evenly and efficiently, consumes much lower power and has longer running life.



Improved chassis and platen!

CNC aluminum beam and silent linear guide assure high speed, high resolution printing and long running life. Angled printing platen gives steady and anti wrinkle media delivery.



Optimized feeding and taking up system!

Feeding system with redesigned media holder is for easier and humanized operation. Taking up system with pneumatic shaft and dancer bar enables more precise taking up.



Panasonic A6 servo system!

Panasonic A6 servo system has higher torque and lower vibration, assuring more stable and precise carriage movement.

ITEM	SPECIFICATION	
Model	GZC 3202SG	
Print Head	2 Stafire 1024 (10pl)	2 Stafire 1024 (25pl)
Ink	C.M.Y.K Solvent / Eco-solvent	
Ink Supply System	Positive Pressure System with ink basket	
Media Type	Banner, Frontlit, Backlit, Vinyl, Film...	
Media Delivery System	Automatic media feeding and taking up system with pneumatic shaft	
Drying System	Pre, mid, post and extended heater + thermal drying system	
Printing Speed	300x400dpi 129m ² /h, 600x400dpi 115m ² /h 300x600dpi 86m ² /h, 600x600dpi 76m ² /h 300x800dpi 67m ² /h, 600x800dpi 59m ² /h	300x400dpi 126m ² /h, 600x400dpi 97m ² /h 300x600dpi 87m ² /h, 600x600dpi 65m ² /h 300x800dpi 68m ² /h, 600x800dpi 51m ² /h
Data Interface	External: USB 2.0 ; Internal: High-speed SCSI	
Working Environment	Temp. 23°C~29°C, Humidity: 50%~80%	
Software	PhotoPRINT / Maintop..... +GZ Control Console	
Power	50Hz/AC 200V+10% 15A(printer) +16A(thermal drying system)	
Installed / Package Size	LxWxH (mm) : 4800 x 1000 x 1500 / 4930 x 1150 x 1690	
G.W. / N.W.	1290kgs / 1060kgs	

Specification are liable to change without prior notice. All trademarks mentioned are property of their respective owners.



Authorised Distributor

MEHTA CAD CAM SYSTEMS PVT. LTD.

Head Office: 4 & 5, 2nd Floor, Sumel Complex,
Opp. GNFC Info Tower, Sarkhej Gandhinagar Road,
Ahmedabad-380 059. INDIA.

Contact:

Tel.: +91-79-26840551 / 26840552 / 26840553

Fax: +91-79-26840554



For Immediate Assistance, Contact on **092276 78044, 092276 78041**



mktg@mehtaindia.com



www.mehtaindia.com