



GZC Plus 3204SG (25PL / 10PL)

Now With

/// ONYX

(optional)







Maximum Four Print Heads in Staggered Way.

Extreme Speed up to 234m²/hr.

Durable Panasonic A6 Servo System.

GenTek Negative Pressure Recirculation System.

Smart energy-saving IR drier.

Dismountable Stand for Lower Transportation Cost.


















Gongzheng High Speed Printer SPECTRA STARFIRE



A wide range of applications solution

With continuous ink recirculation and robust repairable construction, Diamatix Starfire 1024 print head delivers unparalleled saturation and smooth gradient.



©∩Tek negative pressure recirculation solution

GZ dual negative pressure recirculation system with pressure balancing unit and pressure protection unit assures steady ink delivery and minimum maintenance.



Smart IR drier

One-piece IR drier for easy installation and smart synchronizing function could dry the printing efficiently and save the electricity. *Double power than GZC.



Robust, durable and precise body

Reinforced CNC aluminum beam and dual linear guides assure high speed, high resolution printing in a long run.

* Double linear guides than GZC.



Optimized feeding and taking up system

Feeding system with strong media holders is suitable for both light and heavy media. Taking up system with air shaft & dancer bar enables precise and steady rewinding.



Panasonic A6 servo system

Panasonic A6 servo system has high torque and low vibration, assuring more stable and precise carriage movement.

ITEM	SPECIFICATION	
Model	GZC 3204SG Plus	GZC 3202SG Plus
Print Hear	4 Stafire 1024	2 Stafire 1024
Ink	C.M.Y.K Solvent / Eco-solvent	
Ink Supply System	©nTek Negative Pressure System	
Media Type	Banner, Frontlit, Backlit, Vinyl, Film	
Media Delivery System	Automatic media feeding and taking up system with air shaft	
Drying System	Pre, mid, post and extended heater plus smart IR drier	
Printing Speed	300x400dpi 234m²/h, 600x400dpi 209m²/h 300x600dpi 163m²/h, 600x600dpi 146m²/h 300x800dpi 127m²/h, 600x800dpi 112m²/h	300x400dpi 129m²/h, 600x400dpi 115m²/h 300x600dpi 86m²/h, 600x600dpi 76m²/h 300x800dpi 67m²/h, 600x800dpi 59m²/h
Data Interface	External: USB 2.0 ; Internal: High-speed SCSI	
Working Environment	Temp. 23°C~29°C, Humidity: 50%~80%	
Software	PhotoPRINT +GZ Control Console	
Power	50Hz/AC 200V+10% 13A(printer)+34A (IR drier)	
Installed / Package Size	LxWxH (mm) : 4840 x 1995 x 1530 / 5140 x 1150 x 1150	
G.W. / N.W.	1150kgs / 886kgs	

Specification are liable to change without prior notice. All trademarks mentioned are property of their respective owners.



Authorised Distributor

MEHTA CAD CAM SYSTEMS PVT. LTD.

Head Office & Manufacturing Industry Plot No.3, Road No.1, Kathwada GIDC,

Ahmedabad, 382 430, Gujarat, INDIA

Tel.: +91-75750 09626 / 75750 09686 / 75750 09687 / 75750 09688 / 079-2970 0235

Fax.: +91-7926840554









