



FIBER LASER MARKING MACHINE

EVAN-20/30/50/100

EVAN

Features

- ☑ First and last pulse equally useable
- ☑ Bitmap marking compatible
- ☑ High repeatability / stability design
- ☑ Status monitoring and safe shut down
- ☑ High speed marking (MHZ repetition rate)
- ☑ Long Using time : the average using time more than 100000 hours
- ☑ Good stability and free maintenance :
- ☑ No need to maintenance for laser advice
- ☑ High quality gray scale marking

EVAN laser provides a fast, flexible and efficient way to permanently mark a wide variety of materials such as Metals, Plastics, Ceramics, Silicon etc.



Applications

- ☑ Auto Parts
- ☑ Hardware
- ☑ Watch & Clock
- ☑ Marking anodize & painted material
- ☑ Serial Numbers
- ☑ Manufactures Information
- ☑ Barcodes
- ☑ Logos
- ☑ Packaging
- ☑ Solar Industry
- ☑ Medical Device
- ☑ Marking Metal & Plastics
- ☑ Data Codes
- ☑ Materials Flow
- ☑ 2D Data Matrix
- ☑ Graphics



With Safety Enclosure



Rotary Attachment for Cylindrical Marking



Hand Held Equipment



For Online Marking

Highlights

- ☑ High Peak Power
- ☑ Excellent Beam Quality
- ☑ Dynamic Pulse Shape Control
- ☑ Proved Reliability
- ☑ Maintenance Free Operation



Advantages

Fiber lasers are up to ten times more efficient than traditional YAG or Co2 laser systems. Consuming little to no energy when not active, the annual energy saving can attract government grant funded energy efficiency programs for industry.

Fiber lasers have no optic to adjust or align and no lamp to replace. Maintenance is minimal and so utilization and up-times are maximized. The lasers are designed as shop floor industrial tools.



FIBER LASER SOURCE

Specification

Model	Evan-20	Evan-30	Evan-50	Evan-100
Output Power	20W	30W	50W	100W
Wavelength	1064 nm			
Power Adjustment	0 to 100%			
Cooling	Air Cooled			
Min. Line Width	Min. 0.03 mm (Depend on Material)			
Max. Speed	Max. 10000 mm/s (Max. Linear Speed)			
Marking Depth	0.01~0.3 mm (Depends on Material)			
Min Character Height	0.5 mm			
Marking Range	145 mm x 145 mm (Standard) Optional : 100 x 100 mm, 175 x 175 mm, 200 x 200 mm, 270 x 270 mm, 300 x 300 mm			
Supporting Format	PLT, DXF, BMP Files etc. Using SHX TTF Character Storage Directly			
Single Pulse Energy (mj)	1.0@20KHz	1.0@30KHz	1.0@50KHz	1.2@100KHz
Repetition Frequency Range	20-60	30-60	50-100	80-120
Output Power Instability	<5%			
Beam Quality (M ²)	<1.6			
Pulse Width (ns)	120-150@20KHz	120-150@30KHz	120-150@50KHz	200-250@80KHz
Power Supply	AC 220 Volt			
Max Power Consumption (Laser Source)	220 Watt	250 Watt	350 Watt	500 Watt

Specifications are liable to change without prior notice.
Computer system will not be provided with the machine.
Total machine power consumption is 1KW.



Invisible laser radiation avoid eye or skin exposure to direct or scattered radiation.



MADE BY MEHTA, FOR THE WORLD

Manufactured & Marketed by:

MEHTA HITECH INDUSTRIES LTD.
(FORMERLY KNOWN AS MEHTA CAD CAM SYSTEMS PVT. LTD.)

Head Office & Manufacturing Facilities
Plot No. 3, Road No. 1, Kathwada GIDC,
Ahmedabad, 382 430, Gujarat. INDIA

Contact:
Tel.: +91-792970 0235 / 7575009626
Fax.: +91-7926840554



dun & bradstreet

For Immediate Assistance, **Contact 092279 85746, 092276 78044**



mktg@mehtaindia.com



www.mehtaindia.com

DELHI | MUMBAI | CHENNAI | KOLKATA | BANGALORE | HYDERABAD | JAIPUR | RAIPUR | INDORE | LUDHIANA | CHANDIGARH | PUNE | NAGPUR | PATNA | LUCKNOW | SURAT | RAJKOT | RANCHI | BHUBANESHWAR | GUWAHATI | HUBLI | VIJAYWADA | COIMBATORE | COCHIN | AGRA | GOA